



# THE RIGHT EQUIPMENT FOR YOUR BUSINESS



## High-Roof Cargo Van (Up to 9,000 lb. GVW)

- Up to 3,500 lb. payload
- Rear and side cargo doors
- Cargo access door and tie rails
- Cargo lighting
- Backup camera\*
- Refrigerated vans available in select markets
- Collision mitigation system\*†



## High-Roof Cargo Van With Shelves (Up to 9,000 lb. GVW)

- Up to 3,200 lb. payload
- 22" deep adjustable shelves of varying widths
- Cargo access door
- Backup camera\*
- Collision mitigation system\*†
- Rear and side cargo doors



## Electric Cargo Van (Up to 9,500 lb. GVW)

- Up to 3,300 lb. payload
- Rear and side cargo doors
- Blind-spot assist and backup camera\*†
- Usable battery: 67 kWh
- 400V lithium-ion battery
- Available in select markets



## 16' Box Truck (Up to 12,500 lb. GVW)

- Up to 4,300 lb. payload
- Rear roll-up door
- Cargo tie rails
- Translucent roof and cargo lighting
- 1,000 lb. loading ramp
- Backup camera and alarm\*



## 16' Box Truck With Shelves (Up to 12,500 lb. GVW)

- Up to 3,800 lb. payload
- Rear roll-up door
- 24" deep adjustable shelves of varying widths
- Sliding door for curbside access
- 1,000 lb. pull-out ramp



## 16' and 18' Cab Forward Box Truck (Up to 17,500 lb. GVW)

- Up to 7,200 lb. payload
- Rear roll-up door
- Cargo tie rails and E-track
- Translucent roof and cargo lighting
- Up to 2,500 lb. liftgate
- Backup alarm\*
- Refrigerated trucks also available



## 18' to 22' Step Van (19,500+ lb. GVW)

- 10,000+ lb. payload
- 1,000+ cu. ft. of loading space
- Interior shelves
- Backup camera and backup alarm\*
- Anti-lock brakes
- Passenger-side jump seat
- Air conditioning and power steering not included



## Up to 26' Box Truck (26,000 lb. NCDL or 33,000 lb. CDL GVW)

- Up to 17,000 lb. payload
- Rear roll-up door
- Cargo tie rails
- E-track and curbside door\*
- Translucent roof and cargo lighting
- Available with up to 3,000 lb. liftgate, liftgate/ramp combination or 1,000 lb. loading ramp
- Collision mitigation system\*†



## 16' to 26' Refrigerated Truck

- 16' cab forward box truck up to 17,500 lb. GVW and 7,200 lb. payload
- 26' medium-duty box truck up to 26,000 lb. NCDL or 33,000 lb. CDL GVW and 15,000 lb. payload
- Rear roll-up door
- Side door\*
- Cargo lighting and E-track
- Self-contained refrigeration unit
- 2,500 to 3,000 lb. liftgate or ramp
- Backup alarm\*



## Up to 26' Flatbed Truck (26,000 lb. NCDL or 33,000 lb. CDL GVW)

- Up to 18,000 lb. payload
- Side and rear stake racks
- Steel bulkhead
- Adjustable cargo securement straps
- Up to 3,000 lb. liftgate
- Backup alarm\*



## Single-Axle Day Cab Tractor (65,000 lb. combined GVW)

- Up to 160-gallon fuel capacity
- Driver air-ride seat
- Automated/manual overdrive transmission
- Air disc brakes
- Up to 410 HP electronic engine
- Air-ride suspension
- Collision mitigation system\*†
- Bluetooth®\*



## Tandem-Axle Day Cab Tractor (80,000 lb. combined GVW)

- Up to 160-gallon fuel capacity
- Driver air-ride seat
- Automated/manual overdrive transmission
- Air disc brakes
- Up to 435 HP electronic engine
- Sliding fifth wheel
- Air-ride rear suspension
- Collision mitigation system\*†
- Bluetooth®\*



## Tandem-Axle Sleeper Tractor (80,000 lb. combined GVW)

- Up to 220-gallon fuel capacity
- Driver and passenger air-ride seat
- Automated/manual overdrive transmission
- Air disc brakes
- Up to 455 HP electronic engine
- Sliding fifth wheel
- Air-ride suspension
- Double-bunk sleeper
- Air fairing
- Collision mitigation system\*†
- Bluetooth®\*



## 48' and 53' Dry Freight Van Trailer

- Overall height 13'6"
- Outside width 102"
- Inside height 110"
- Fifth wheel height 48"
- King pin location 36"
- Sliding tandem axle
- Translucent or aluminum roof
- Rear swing or roll-up doors
- E-track or logistics posts
- Air-ride suspension



## 48' Flatbed Trailer

- Bulkhead height 48"
- Outside width 102"
- King pin location 36"
- Tandem axle, slide spring suspension
- 10 sliding winches – 5 per side



## 53' Refrigerated Trailer

- Overall height 13'6"
- Outside width 102"
- Inside width 96"
- Fifth wheel height 47"
- King pin location 36"
- Sliding tandem axle
- Rear swing or roll-up doors
- Single-temperature, electric standby and low hours

Truck images are for illustrative purposes only. Actual trucks may vary by make, model and year.

All trucks are equipped with automatic/automated manual transmission, radio with AUX or USB input, air conditioning, power steering and anti-lock brakes.

All tractors are equipped with radio with AUX or USB input, air conditioning and power steering.

\*Available on select models

† While many vehicles will have some form of collision mitigation systems, the presence of such systems cannot be guaranteed. Please check with Penske at the time of rental.